

Digital Image Processing

Kenneth R. Castleman

2008/2/26

Presentation by S. Wang

Shuozhong Wang, SCIE, Shanghai University

Part One - 3

Fundamentals

Algebraic operations

Geometric transform

Shuozhong Wang, SCIE, Shanghai University

Chapter 7

Algebraic Operations

Shuozhong Wang, SCIE, Shanghai University

Introduction



- Algebraic operations produce an image which is pixel-by-pixel sum, difference, product, or quotient of two input images:

$$C(x, y) = A(x, y) + B(x, y)$$

$$C(x, y) = A(x, y) - B(x, y)$$

$$C(x, y) = A(x, y) \times B(x, y)$$

$$C(x, y) = A(x, y) \div B(x, y)$$

- The resulting pixel values must be integers within a given range, e.g., 0-255. Rounding and clipping is necessary.
- $B(x, y)$ may be a constant, which changes the overall brightness of $A(x, y)$.

Shuozhong Wang, SCIE, Shanghai University

Applications



- Addition
 - Produce multiple exposure effects
 - Average several images of the same scene to reduce noise.
- Subtraction
 - Remove unwanted contents
 - Detect moving objects
 - Calculate gradient to extract edges
- Multiplication
 - Correct digitizing errors or illumination non-linearity
 - Change color balance
 - Create special effects
- Division
 - Detect changes
 - Correct uneven illumination
 - Process multispectral images

Algebraic Operations and Histogram



- Find the histogram of sum images:

$$C(x, y) = A(x, y) + B(x, y)$$
- Assume A and B are uncorrelated. Joint 2-D histogram:

$$H(D_A, D_B) = H_A(D_A) H_B(D_B)$$
- To reduce the 2D histogram to a 1D marginal histogram:

$$H(D_A) = \int_{-\infty}^{\infty} H_{AB}(D_A, D_B) dD_B = \int_{-\infty}^{\infty} H_A(D_A) H_B(D_B) dD_B$$
- Taking into account relationship among D_A , D_B and D_C :

$$H(D) = \int_{-\infty}^{\infty} H_A(D_C - D_B) H_B(D_B) dD_B$$
- The right side is a function of D_C . Thus

$$H_C(D) = H_A(D) * H_B(D)$$

Histogram of Sum Images: an Example



- Supposing two images have Gaussian histograms, the sum image also has a Gaussian histogram.
 - The mean equal to the sum of individual means, and
 - The variance equal to the sum of individual variances.

$$H_i(x) = A_i \exp\left[-\frac{(x - \mu_i)^2}{2\sigma_i^2}\right], \quad i = 1, 2$$



$$H_1(x) * H_2(x) = A_1 A_2 \sqrt{2\pi\sigma_1\sigma_2} \exp\left[-\frac{(x - (\mu_1 + \mu_2))^2}{2(\sigma_1^2 + \sigma_2^2)}\right]$$

- The convolution formula still holds as long as one of the images is changed to its negative.

Averaging for Noise Reduction



- Consider a number of exposures taken on the same scene, each with independent additive noise:

$$D_i(x, y) = S(x, y) + N_i(x, y), \quad i = 1, 2, \dots, M$$
- $N_i(x, y)$ is an independent sample of zero mean noise field:

$$\begin{aligned} E[N_i(x, y)] &= 0 \\ E[N_i(x, y)N_j(x, y)] &= 0 \end{aligned}$$
- Signal-to-noise power ratio of individual images:

$$P(x, y) = S^2(x, y) / E[N^2(x, y)]$$

Averaging for Noise Reduction (cont.)



- Average of M images:

$$\bar{D}(x, y) = \frac{1}{M} \sum_{i=1}^M [S(x, y) + N_i(x, y)]$$

Demo_Algebra1
Demo_NoiseAv

- Signal-to-noise power ratio $P(x, y)$ is increased by a factor of M , or, SNR is increased by $10 \log M$ dB:

$$\bar{P}(x, y) = M P(x, y)$$

- An example.
- Try to write a program to verify this conclusion.
- Demo: Demo_Algebra1. (Code)

Image Subtraction



- Background subtraction: see Fig.7-3 on p.109 (removing the uneven illumination field effect)
- Motion detection: see Fig.7-4 on p.110 (removing stationary freeway to show the moving vehicles)

- Gradient magnitude:

- The gradient field:

$$\nabla f(x, y) = \vec{i} \frac{\partial f(x, y)}{\partial x} + \vec{j} \frac{\partial f(x, y)}{\partial y}$$

- The gradient magnitude:

$$|\nabla f(x, y)| = \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$$

- To avoid calculating square roots:

$$|\nabla f(x, y)| \approx \max[|f(x, y) - f(x + \Delta x, y)|, |f(x, y) - f(x, y + \Delta y)|]$$

Image subtraction

Summary of Algebraic Operations



- The histogram of a sum image is convolution of the histograms of the two component images.
- Convolution of two Gaussian functions produces a broader Gaussian, with the means and variances added.
- Averaging M images increases the SNR by $10 \log M$ dB.
- Subtracting slightly offset images gives a partial derivative image.

Summary of Algebraic Operations (cont.)



- Image multiplication can be used to mask unwanted areas in an image by setting the multiplier to zero.
- Image division is useful in removing spatially varying digitizer sensitivity function.
- Multispectral image processing will be discussed later.
- Problems of Chapter 7: p.113, 4

Chapter 8

Geometric Operation

Shuozhong Wang, SCIE, Shanghai University

Introduction



- Geometric transform changes spatial relationships among objects in an image: Moving things around (like stretching a rubber sheet).
- Constraints: pixel order is preserved so that no random scrambling of pixels occurs.
- Two basic operations involved:
 - Spatial transformation
 - Gray level interpolation

Shuozhong Wang, SCIE, Shanghai University

13

Introduction: Spatial Transformation



- It is desirable to preserve continuity of curvilinear features and connectivity of objects.
- General definition of spatial transformation:

$$g(x, y) = f(x', y') = f[a(x, y), b(x, y)]$$

where $f(x, y)$ is the input image, and $g(x, y)$ is the output.

Shuozhong Wang, SCIE, Shanghai University

14

Spatial Transformation (cont.)



- Connectivity is preserved if $a(x, y)$ and $b(x, y)$ are continuous.
- Gray levels in the input image are defined at integer values of (x, y) , while in the output image, $g(x, y)$ may be taken from $f(x, y)$ at **fractional** coordinate positions.
- Two possibilities:
 - Pixels in $f \rightarrow$ Positions between pixels in g
 - Positions between pixels in $f \rightarrow$ Pixels in g


Shuozhong Wang, SCIE, Shanghai University

15

Introduction: Gray Level Interpolation




- Two approaches:



Forward mapping (pixel carryover)

A pixel value is divided into four parts.




Backward mapping (pixel filling)

Four pixel values are combined into one.

Forward Mapping



- Each output pixel may be addressed several times.
- Many input pixels may fall outside output range: a waste.
- If image is enlarged, some output pixels may be missed.
- If the size is reduced, more than 4 input pixels may contribute to an output pixel.




Forward mapping (pixel carryover)

Backward Mapping



- Output pixels are generated line-by-line and point-by-point.
- Each output pixel is contributed by 4 input pixels.
- Input pixels are accessed randomly.
- It is a more practical way of doing interpolation.




Backward mapping (pixel filling)

Gray-Level Interpolation Methods



- Using backward mapping, output pixels generally map to somewhere between four input pixels.
- Zero-order technique: Nearest neighbor interpolation:
 - Computationally simple.
 - Artifacts may occur in areas with fine details (see Fig.8-2).




Nearest neighbor interpolation

Bilinear Interpolation (1)



- It is a first-order technique, which gives a more desirable result with only slightly increased computation complexity.
- Fitting a plane from 4 points is **over-determined**. A bilinear function is required to interpolate on a rectangular grid.
- Problem: Find $f(x,y)$ given $f(0,0)$, $f(1,0)$, $f(0,1)$, and $f(1,1)$.



Shuozhong Wang, SCIE, Shanghai University


20

Bilinear Interpolation (2)



- Assume that $f(x,y)$ is on a **hyperbolic paraboloid** defined by the following bilinear equation:

$$f(x, y) = ax + by + cxy + d$$



Shuozhong Wang, SCIE, Shanghai University

21

Bilinear Interpolation (3)



- Linear interpolate from $f(0,0)$ and $f(1,0)$ to $f(x,0)$, and from $f(0,1)$ and $f(1,1)$ to $f(x,1)$:

$$f(x,0) = f(0,0) + x[f(1,0) - f(0,0)]$$

$$f(x,1) = f(0,1) + x[f(1,1) - f(0,1)]$$


- Linear interpolate from $f(x,0)$ and $f(x,1)$ to $f(x,y)$:

$$f(x, y) = f(x,0) + y[f(x,1) - f(x,0)]$$

Computation Complexity:

6 Additions +

3 Multiplications



Shuozhong Wang, SCIE, Shanghai University

22

Bilinear Interpolation (4)




- Combine the above three equations into one:

$$f(x, y) = [f(1,0) - f(0,0)]x + [f(0,1) - f(0,0)]y + [f(1,1) + f(0,0) - f(0,1) - f(1,0)]xy + f(0,0)$$

Computation Complexity:

8 Additions +

4 Multiplications




Shuozhong Wang, SCIE, Shanghai University

23

Bilinear Interpolation (5)



- Intersection of the hyperbolic paraboloid in x-z and y-z planes are straight lines.
- Gray-levels across neighboring grids are continuous.
- Slopes (gradients) are not continuous.



Demo_Bilinear.m

Shuozhong Wang, SCIE, Shanghai University

24

High Order Interpolation



- High-order interpolation is used when
 - Higher resolution is required, or
 - Slope discontinuity is not tolerable.
- High-order interpolation can be done by solving an equation more complicated with more than 4 coefficients.
- Some high order techniques:
 - Cubic spline
 - Legendre centered function
 - Sinc function

Shuozhong Wang, SCIE, Shanghai University

25

Spatial Transformation



- The general form:

$$g(x, y) = f(x', y') = f[a(x, y), b(x, y)]$$

- **Simple transformations**

- Identity operation:

$$\begin{cases} a(x, y) = x \\ b(x, y) = y \end{cases}$$

- Translation:

$$\begin{cases} a(x, y) = x + x_0 \\ b(x, y) = y + y_0 \end{cases}$$

Or, in matrix form
(in the homogeneous coordinates):

$$\begin{bmatrix} a(x, y) \\ b(x, y) \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & x_0 \\ 0 & 1 & y_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

Shuozhong Wang, SCIE, Shanghai University

26

Spatial Transformation (cont.)



- Magnification:

$$\begin{cases} a(x, y) = x / c \\ b(x, y) = y / d \end{cases}$$

or, in matrix:

$$\begin{bmatrix} a(x, y) \\ b(x, y) \\ 1 \end{bmatrix} = \begin{bmatrix} 1/c & 0 & 0 \\ 0 & 1/d & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

- Reflection about y axis:

$$\begin{cases} a(x, y) = -x \\ b(x, y) = y \end{cases}$$

or:

$$\begin{bmatrix} a(x, y) \\ b(x, y) \\ 1 \end{bmatrix} = \begin{bmatrix} -1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

Shuozhong Wang, SCIE, Shanghai University


27

Spatial Transformation (cont.)



- Rotation by an angle θ :

$$\begin{cases} a(x, y) = x \cos \theta - y \sin \theta \\ b(x, y) = x \sin \theta + y \cos \theta \end{cases}$$



In the matrix form:

$$\begin{bmatrix} a(x, y) \\ b(x, y) \\ 1 \end{bmatrix} = \begin{bmatrix} \cos \theta & -\sin \theta & 0 \\ \sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

Spatial Transformation (cont.)



- Rotation by θ about $(x_0, y_0) \Rightarrow$ combination of rotation and translation:

- First, translate the image to make (x_0, y_0) the origin.
- Rotate by θ , and
- Translate back to restore the origin.

$$\begin{aligned} \begin{bmatrix} a(x, y) \\ b(x, y) \\ 1 \end{bmatrix} &= \begin{bmatrix} 1 & 0 & x_0 \\ 0 & 1 & y_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos \theta & -\sin \theta & 0 \\ \sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 & -x_0 \\ 0 & 1 & -y_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix} \\ &= \begin{bmatrix} \cos \theta & -\sin \theta & -x_0 \cos \theta + y_0 \sin \theta + x_0 \\ \sin \theta & \cos \theta & -x_0 \sin \theta - y_0 \cos \theta + y_0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix} \end{aligned}$$

Separable Implementations



- It is easy to separate translation and magnification into two steps, for example, horizontal first, and then vertical.
- It is also possible to perform a rotation in two steps.

$$\begin{cases} a(x, y) = x \cos \theta - y \sin \theta \\ b(x, y) = x \sin \theta + y \cos \theta \end{cases}$$



Solving the first equation for x :

$$x = \frac{a(x, y) + y \sin \theta}{\cos \theta}$$

Substituting into the 2nd equation:

$$b(x, y) = \frac{a(x, y) \sin \theta + y}{\cos \theta}$$

Separable Implementations (cont.)



- Having obtained the equations

$$x = \frac{a(x, y) + y \sin \theta}{\cos \theta} \quad \& \quad b(x, y) = \frac{a(x, y) \sin \theta + y}{\cos \theta}$$

a two-step rotation can be performed as follows.

Step 1: keep y unchanged:

$$\begin{cases} a'(x, y) = x \cos \theta - y \sin \theta \\ b'(x, y) = y \end{cases}$$

Step 2: keep the obtained $a(x, y)$:

$$\begin{cases} a(x, y) = a'(x, y) \\ b(x, y) = \frac{a'(x, y) \sin \theta + y}{\cos \theta} \end{cases}$$

Demo_Rotate.m

General Transformations



- Analytical expressions generally do not exist. Transform may be got from measurements. For example (Fig.8-4):
 - Take the first shot on a grid pattern,
 - Calculate the transformation numerically from the grid, and
 - Apply the obtained transformation to subsequent shots.
- Control point approach: Only a small number of pixels are specified, and most pixels are corrected by interpolation.
- Polynomial fitting:
 - Determined: No. of polynomial coefficients = No. of control points
 - Over-determined or under-determined: pseudo-inversion technique
- Piecewise bilinear interpolation

Applications of Geometrical Operations






- Geometric calibration — To remove camera-induced geometric distortion.
- Image rectification — To correct non-rectangular pixel coordinates. (also see Fig.8-8, Fig.8-9)
- Image registration — To register images for comparison.
 - MRI image registration
 - Anti-attack watermark detection
 - Motion detection
- Image format conversion (Fig.8-10)
- Map projection (for self-reading)
- Morphing for special effects (Fig.8-17)
- Problems of Chapter 8: p.138, 1,4,



More
examples

End of Part One

Histogram of Negative Image




Noise Reduction by Image Averaging



Code for Noise Reduction by Averaging (1)



```
(get image F0, sized [M,N])
K=20;           % Number of images
S=20;           % Noise magnitude
F=zeros(M,N,K);
for k=1:K       % 20 noisy images
    F(:, :, k)=S*randn(M,N)+F0;
end
img4a(F0,[10 480],'Clean Image');
img4a(F(:, :, 1),[20+M 480],'Noisy Image');
IM=img4a(F(:, :, 1),[30+2*M 480]);
```



Shuozhong Wang, SCIE, Shanghai University


Code for Noise Reduction by Averaging (2)



```
% Histogram of clean image
figure('Pos',[10 400-N M N]);
imhist(uint8(F0),256);

% Histogram of noisy image
figure('Pos',[20+M 400-N M N]);
imhist(uint8(F(:, :, 1)),256);

% Histogram of noisy image
FG=figure('Pos',[30+2*M 400-N M N]);
imhist(uint8(F(:, :, 1)),256);
```




Shuozhong Wang, SCIE, Shanghai University

Code for Noise Reduction by Averaging (3)



```
for k=1:K
    Fbar=F0;
    for l=1:k,           % averaging
        Fbar=Fbar+F(:, :, l);
    end
    Fbar=clip(round(Fbar/k),0,255);
    close(IM);
    IM=img4a(Fbar);
    close(FG);
    FG=figure;
    imhist(uint8(Fbar),256);
    pause;
end
```



Shuozhong Wang, SCIE, Shanghai University

Exercise: P.113_4



```
H1=[0 100 400 700 800 600 500 600 500 400 400 600 400 100 0 0];
H2=[0 100 300 700 700 600 500 600 500 400 400 600 500 200 0 0];
```

```
% Histogram of the difference image: Im2-Im1:
H3=conv2(H2,H1(16:-1:1));
```



```
M=sum(H1(:));
figure('Pos',[10 300 300 220],'Units','norm');
axes('Pos',[.1 .1 .86 .86]);
stem(0:15,H1);
figure('Pos',[10 300 300 220],'Units','norm');
axes('Pos',[.1 .1 .86 .86]);
stem(0:15,H2);
figure('Pos',[10 300 600 220],'Units','norm');
axes('Pos',[.1 .1 .86 .86]);
stem(-15:15,H3/M);
```

```
H3=round(H3/M);      % Histogram of difference image
```

Shuozhong Wang, SCIE, Shanghai University

40

Exercise: P.113_4 (cont.)



```
H3=[0 0 0 2 11 41 93 151 190 228 277 331 372 425 495 541
518 456 403 362 311 261 225 187 130 66 21 3 0 0 0]
```

Shuozhong Wang, SCIE, Shanghai University

41

Addition: Multiple Exposure



Shuozhong Wang, SCIE, Shanghai University

42

Addition: Multiple Exposure Effects



[Go back](#)

Shuozhong Wang, SCIE, Shanghai University

43

Image Subtraction



Shuozhong Wang, SCIE, Shanghai University


44

Subtraction: Detection of Moving Objects



Moving objects in a video sequence can be detected by pixel subtraction.

[Go back](#)



Shuozhong Wang, SCIE, Shanghai University

45

Subtraction: Background Removal



Shuozhong Wang, SCIE, Shanghai University

46

Subtraction: Edge Extraction



- Detection of motion or slight changes: difference of two nearly-identical and slightly offset images:

$$C(x, y) = A(x, y) - A(x + \Delta x, y) \approx \frac{\partial}{\partial x} A(x, y) \Delta x$$



Shuozhong Wang, SCIE, Shanghai University

47


Multiplication: Correct Brightness




Multiplication: Color Balance Correction




- Suppose an image is too pink (too red and too blue), but its green channel is just fine.
- To reduce red and blue, multiply them by a percentage less than 100%. Example: multiply it by (0.87, 1.00, 0.95).
- Multiplication by a color is analogous to looking through a filter of that color.
- Looking at the overly-magenta image through a "pale green" filter will correct the image.



Addition and Multiplication




Division: Detection of Changes



Slight changes in image can be detected using pixel division.

Division: Correct Uneven Illumination



$$B(x, y) \propto I(x, y) R(x, y)$$

$$\frac{B_{orig}(x, y)}{B_{blank}(x, y)} \propto \frac{I_{orig}(x, y) R_{orig}(x, y)}{I_{blank}(x, y) R_{blank}(x, y)}$$

$$\frac{B_{orig}(x, y)}{B_{blank}(x, y)} \propto R_{orig}(x, y)$$

1. Same illumination:
 $I_{orig} = I_{blank}$
2. Reflectivity of blank paper is constant.
3. Even background obtained by division.

Shuozhong Wang, SCIE, Shanghai University


52

Multispectral Images: Flood Assessment



Flood assessment:
Surat Thani, Thailand

Image arithmetic
operations, neural
networks and image
fusion are used.



Shuozhong Wang, SCIE, Shanghai University

53


Correction of Geometric Distortion



Shuozhong Wang, SCIE, Shanghai University

54

Correction of Lens Distortion



Shuozhong Wang, SCIE, Shanghai University

55

Correction of Lens Distortion

